DYNAMO LUBRICANTS

BOLDLY EXCEEDING EXPECTATIONS.

DYNALUX CA

CALCIUM BASE PREMIUM GREASE

Dynalux CA is a premium quality calcium base grease, specially developed for the lubrication of automotive chassis parts. It possesses strong affinity for metal surfaces with extremely good stay-put properties and adequate water

resistance. As a result, the applied lubricant film is not displaced even under repeated shock-loads and vibrations.

Dynalux CA greases are available in NLGI 1, 2, 3.

FEATURES & BENEFITS

- Provides excellent resistance to water wash and displacement under shock-loads.
- Ensures protection against wear by preventing metal to metal contact.
- Has equally good dispensing qualities in summer and winter.
- Provides protective coating to exposed parts of equipment, during temporary storage

APPLICATION

Dynalux CA grease has adequate consistency to serve as an effective heavy duty chassis grease, with high load carrying ability. It is suitable for all chassis parts including suspension and steering system of automobiles. This grease can also be recommended for open and semi enclosed gearings and chain drives of farm equipment.

SPECIFICATION OF DYNALUX CA

PARAMETERS	Dynalux CA 1	Dynalux CA 2	Dynalux CA 3
NLGI Grade	1	2	3
Thickener Type	Calcium	Calcium	Calcium
Color, Visual	Amber	Amber	Amber
Penetration, Worked, 25°C, ASTM D 217	325	280	235
Viscosity of Oil, ASTM D 445			
cSt ⊚ 40°C	110	110	110
Dropping Point, D 2265, C	90	90	90

These characteristics are typical of current production.

Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.



