



BOLDLY EXCEEDING EXPECTATIONS.

**DYNAMO
LUBRICANTS**

DYNA GOLD, API SF / CD, SAE 20W50 MULTIGRADE ENGINE OIL

Dyna Gold API SF / CD, SAE 20W50 is a multigrade diesel & petrol engine oil formulated with an

optimised combination of base oils and a balanced additive system.

FEATURES & BENEFITS

- Good protection against rust and corrosion for longer equipment life and reduced operating costs.
- Thermal and oxidation stability that controls sludge build-up and deposits

APPLICATION

Gasoline and diesel powered equipment where API SF / CD level performance is required. On-highway light and medium duty trucking. Off-highway industries including: construction,

quarrying, and agriculture.

It is also available in other SAE grades in 200 litres packing: 15W40, 30, 40 & 50

SPECIFICATION OF DYNA GOLD, API CD / SF, SAE 20W50, 15W40, 30, 40 & 50

PARAMETERS	SAE20W50	SAE15W40	SAE30	SAE40	SAE50
Viscosity, ASTM D 445					
cSt @ 40 Deg C	176.8	126.5	107.12	141.4	171.3
cSt @ 100 Deg C	17.93	14.42	11.15	14.6	17.42
Viscosity Index, ASTM D 2270	111	114	88	102	110
Total Base mg KOH/g, ASTM D 2896	5	5	5	5	5
Pour Point, Deg C, ASTM D 97	-9	-9	-9	-9	-9
Flash Point, Deg C, ASTM D 93	224	218	220	224	218
Density @ 30 Deg C Kg/L, ASTM D 4052	0.8844	0.8786	0.8870	0.8851	0.8844
Colour ASTM D 1500	L3	L2.5	L2.5	L2.5	L2.5

These characteristics are typical of current production.

Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.

MANUFACTURED BY
D.K. LUBRICANTS (M) SDN BHD
SELANGOR D.E., MALAYSIA

INTERNATIONALLY MARKETED BY
KISMAT PETROLEUM TRADING PTE LTD,
SINGAPORE



DYNAMOLUBRICANTS.COM