



# BOLDLY EXCEEDING EXPECTATIONS.

**DYNAMO  
LUBRICANTS**

## DYNA POWER, API CF4/CF/SG, SAE 15W40 & 20W50 HIGH PERFORMANCE DIESEL ENGINE OIL

Dyna Power API CF4/CF/SG is a high-performance diesel engine oil that provides proven protection of diesel engines operating in severe conditions for both on and off-highway applications. Dyna Power API CF4/CF/SG primarily intended for use in Diesel Commercial Vehicles. The technology in Dyna

Power API CF4/CF/SG delivers excellent performance in both modern diesel engines as well as older models.

Dyna Power is available in two multi-viscosity grades: SAE 15W40 and 20W50.

### FEATURES & BENEFITS

- Thermal and oxidation stability that controls sludge build-up and deposits.
- TBN reserve for deposit control.
- Stay-in-grade shear stability that reduces oil consumption and wear protection.
- Excellent detergency/dispersancy for cleaner engines and longer engine life.
- Component compatibility that longer gasket and seal life

### APPLICATION

It is designed as per requirement of Engine oil for use in all Commercial vehicle diesel engines where API CF4/CF/SG or lower Engine Oil is required.

Can be used in many turbocharged engines to provide protection and long engine life.

Suitable for most gasoline and heavy diesel engines minimising the need to carry multiple oil needs for different vehicles.

Can also be used in non-turbo charged engines under normal conditions.

### SPECIFICATION OF DYNA POWER, API CF4/CF/SG, SAE 15W40 & 20W50

PARAMETERS	TYPICAL PROPERTIES SAE 15W40	TYPICAL PROPERTIES SAE 20W50
<b>Viscosity, ASTM D 445</b>		
cSt @ 40 Deg C	105	172.3
cSt @ 100 Deg C	14.5	20.8
Viscosity Index, ASTM D 2270	142	142
Sulphated Ash, wt%, ASTM D 874	1.15	1.15
Total Base mg KOH/g, ASTM D 2896	9	9
Pour Point, Deg C, ASTM D 97	-33	-30
Flash Point, Deg C, ASTM D 92	230	232
Density @ 15 Deg C Kg/L, ASTM D 4052	0.880	0.880

These characteristics are typical of current production. Whilst future production will conform to Dynamo specification, variations in these characteristics may occur.

**MANUFACTURED BY**  
D.K. LUBRICANTS (M) SDN BHD  
SELANGOR D.E., MALAYSIA

**INTERNATIONALLY MARKETED BY**  
KISMAT PETROLEUM TRADING PTE LTD,  
SINGAPORE



**DYNAMOLUBRICANTS.COM**